

Charging Tesla cars with CHAdeMO connector

***) using CHAdeMO adapter**

- 1) Open the cover of the car's charging connector;
- 2) Activate the charging station with an RFID card or mobile application;
- 3) Select the CHAdeMO charging connector on the station monitor when prompted;
- 4) When the charging station asks you to add a car - Connect the CHAdeMO charging connector to the Tesla - CHAdeMO adapter;
- 5) Connect the Tesla - CHAdeMO adapter to the Tesla car charging socket;
- 6) The station will perform the necessary checks and charging will begin.

Charging Tesla cars with CCS connector

***) using CCS adapter**

There are several scenarios depending on the version of the Tesla car software:

A	B
<ol style="list-style-type: none">1) Open the cover of the car's charging connector;2) Connect the adapter to the CCS connector;3) Activate the charging station with the RFID card or mobile application;4) Connect the CCS connector with adapter to the Tesla car charging socket;5) Select the CCS Charging Connector on the Station Monitor;6) The station will perform the necessary checks and charging will begin.	<ol style="list-style-type: none">1) Open the cover of the car's charging connector;2) Connect the CCS adapter to the car connector;3) Activate the charging station with the RFID card or mobile application;4) Connect the CCS connector to the adapter plugged into the car charger socket;5) Select the CCS Charging Connector on the Station Monitor;6) The station will perform the necessary checks and charging will begin. <p>!!! In some cases, an algorithm with 4) and 5) in reverse order may work</p>

***) if the CCS connector socket is built into the car**

- 1) Open the cover of the car's charging connector;
- 2) Activate the charging station with an RFID card or mobile application;
- 3) Connect the CCS connector to the Tesla car charging socket;
- 4) Select the CCS Charging Connector on the Station Monitor when prompted;
- 5) The station will perform the necessary checks and charging will begin.